


K-BOX CLICK-CLOCK

Boxed set - click-clock

HANSA FLEX

Omadused

| | |
|----------------|--------------------|
| Töörõhk | Max. 16 bar |
| Töötemperatuur | -20 °C to +80 °C |
| Materjal | Nikeldatud messing |
| Surverõngas | Hostaform |
| O-rõngas | NBR |
| Pingutusrõngas | Stainless steel |



Kirjeldus

45 male connectors G 1/8-4, G 1/8-6, G 1/4-8, G 3/8-8
35 swivel type male elbows G 1/8-4, G 1/8-6, G 1/4-6, G 1/4-8, G 3/8-8
15 unions 4, 6, 8 mm
10 union elbows 6, 8 mm
15 union tees 4, 6, 8 mm
15 swivel type male branch tees G 1/8-6, G 1/4-6, G 1/4-8
9 reducers with push-in plug 8/6, 10/6, 10/8
10 plugs 6, 8 mm
10 sockets G 1/8, G 1/4, G 3/8
1 PTFE-sealing tape
1 hose cutter

Lisateave

Further types and dimensions on request.

Artikkel

| Märgistus | Definitsioon |
|----------------|--|
| K- 07 40 35 24 | Boxed set, >click-clock< Series push-in fittings |