

K-DMUF FESTSTOFFHALTIGE MED

Pressure transmitter for viscous and solids-containing media, nonlinearity 0.2%

HANSA FLEX

Omadused

Tüüp	S-11
Pinge	DC 10 (14) ... 30 V
Elektriühendus	With right-angle connector acc. to DIN EN 175301-803 A
Kaitse tüüp	IP 65 acc. to EN 60529
Väljundsignaal	4 to 20 mA, 2-wire
Mittelineaarsus	0.2% of span
Aine temperatuur	-30 °C to +100 °C; (Range: 400 and 600 bar: -30 °C to +70 °C)
Keskonnatemperatuur	-20 °C to +80 °C
Mõõteainega kokkupuutuvad osad	CrNi steel 1.4571
Korpus	CrNi steel 1.4571



Kirjeldus

Pressure transmitter in CrNi steel with flush diaphragm for measuring viscous, pasty, adhesive, crystallising, particle-laden or contaminated media, which would clog the pressure channel of conventional process connections. Applications: Electronic pressure measurement in the food and beverages sector, hydraulic power units or industrial applications in general.

Lisateave

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

Artikkel

Märgistus	Mõõteulatus	Keere
K- 07 20 12 38	0 - 0.25 bar	G 1
K- 07 20 12 39	0 - 0.4 bar	G 1
K- 07 20 12 40	0 - 1.0 bar	G 1
K- 07 20 12 41	0 - 10.0 bar	G 1/2
K- 07 20 12 42	0 - 100.0 bar	G 1/2
K- 07 20 12 43	0 - 16.0 bar	G 1/2
K- 07 20 12 44	0 - 160.0 bar	G 1/2
K- 07 20 12 45	0 - 25.0 bar	G 1/2
K- 07 20 12 46	0 - 250.0 bar	G 1/2
K- 07 20 12 47	0 - 4.0 bar	G 1/2
K- 07 20 12 48	0 - 40.0 bar	G 1/2
K- 07 20 12 49	0 - 400.0 bar	G 1/2
K- 07 20 12 50	0 - 6.0 bar	G 1/2
K- 07 20 12 51	0 - 60.0 bar	G 1/2
K- 07 20 12 52	0 - 600.0 bar	G 1/2

Varuosad

K-ZUBEH DRUCKMESSUMFOR Accessoirs for pressure transmitters for viscous and solids-containing media, nonlinearity 0.2%