


# K-L-STECKVER DREH AG-K BESCH

Male elbows, swivel type, conical male thread, coated

**HANSA FLEX**

## Omadused

|                     |  |
|---------------------|--|
| Töörõhk             | Max. 15 bar, coarse vacuum   |
| Rakendusvaldkond    | Air, vacuum  |
| soovitatud voolikud | PU or PA (nylon)   |
| Vahendid            | Compressed air and all gases or liquids that are compatible with the materials |
| Temperatuuri ulatus | -20 °C to +80 °C   |
| Tihenduspinid       | Conical version: thread coating  |
| Materjal            | Plastic, Nickel plated brass   |
| Surverõngas         | Plastic  |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Artikkel

| Märgistus      | Keere | vooliku välimise-Ø jaoks (mm) | L1 (mm) | L2 (mm) | SW    |
|----------------|-------|-------------------------------|---------|---------|-------|
| K- 07 40 01 68 | R 1/8 | 4 mm                          | 18,8    | 18,5    | 10 mm |
| K- 07 40 01 69 | R 1/8 | 6 mm                          | 20,0    | 19,5    | 10 mm |
| K- 07 40 01 70 | R 1/8 | 8 mm                          | 22,5    | 22,9    | 10 mm |
| K- 07 40 01 65 | R 1/4 | 4 mm                          | 18,8    | 20,0    | 14 mm |
| K- 07 40 01 66 | R 1/4 | 6 mm                          | 20,0    | 21,0    | 14 mm |
| K- 07 40 01 67 | R 1/4 | 8 mm                          | 22,5    | 21,5    | 14 mm |
| K- 07 40 01 63 | R 1/4 | 10 mm                         | 26,9    | 26,3    | 17 mm |
| K- 07 40 01 64 | R 1/4 | 12 mm                         | 28,5    | 27,8    | 17 mm |
| K- 07 40 01 74 | R 3/8 | 6 mm                          | 20,0    | 22,5    | 17 mm |
| K- 07 40 01 75 | R 3/8 | 8 mm                          | 22,5    | 23,0    | 17 mm |
| K- 07 40 01 71 | R 3/8 | 10 mm                         | 26,9    | 24,8    | 17 mm |
| K- 07 40 01 72 | R 3/8 | 12 mm                         | 28,5    | 26,3    | 17 mm |
| K- 07 40 01 73 | R 3/8 | 16 mm                         | 33,5    | 33,7    | 20 mm |
| K- 07 40 01 61 | R 1/2 | 6 mm                          | 20,0    | 25,5    | 21 mm |
| K- 07 40 01 62 | R 1/2 | 8 mm                          | 22,5    | 26,0    | 21 mm |
| K- 07 40 01 58 | R 1/2 | 10 mm                         | 26,9    | 27,8    | 21 mm |
| K- 07 40 01 59 | R 1/2 | 12 mm                         | 28,5    | 29,3    | 21 mm |
| K- 07 40 01 60 | R 1/2 | 16 mm                         | 33,5    | 36,7    | 21 mm |