

K-L-STECKVER L DREH AG-K

Male elbows, long, swivel type, conical male thread, coated

HANSA FLEX

Omadused

| | |
|---------------------|--|
| Töörõhk | Max. 15 bar, coarse vacuum |
| Rakendusvaldkond | Air, vacuum |
| soovitatud voolikud | PU or PA (nylon) |
| Vahendid | Compressed air and all gases or liquids that are compatible with the materials |
| Temperatuuri ulatus | -20 °C to +80 °C |
| Tihenduspeind | Conical version: thread coating |
| Materjal | Plastic, Nickel plated brass |
| Surverõngas | Plastic |



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Artikkel

| Märgistus | Keere | vooliku välimise-Ø jaoks (mm) | L1 (mm) | L2 (mm) | SW |
|----------------|-------|-------------------------------|------------|------------|-------|
| K- 07 40 02 10 | R 1/8 | 4 mm | 18,8 | 32,5 | 10 mm |
| K- 07 40 02 11 | R 1/8 | 6 mm | 20,0 | 33,5 | 10 mm |
| K- 07 40 02 12 | R 1/8 | 8 mm | 22,5 | 38,7 | 10 mm |
| K- 07 40 02 08 | R 1/8 | 10 mm | 26,9 | 46,4 | 17 mm |
| K- 07 40 02 09 | R 1/8 | 12 mm | 28,5 | 47,9 | 17 mm |
| K- 07 40 02 05 | R 1/4 | 4 mm | 18,8 | 34,0 | 14 mm |
| K- 07 40 02 06 | R 1/4 | 6 mm | 20,0 | 35,0 | 14 mm |
| K- 07 40 02 07 | R 1/4 | 8 mm | 22,5 | 37,3 | 14 mm |
| K- 07 40 02 03 | R 1/4 | 10 mm | 26,9 | 48,4 | 17 mm |
| K- 07 40 02 04 | R 1/4 | 12 mm | 28,5 | 49,9 | 17 mm |
| K- 07 40 02 16 | R 3/8 | 6 mm | 20,0 | 36,5 | 17 mm |
| K- 07 40 02 17 | R 3/8 | 8 mm | 22,5 | 38,8 | 17 mm |
| K- 07 40 02 13 | R 3/8 | 10 mm | 26,9 | 46,9 | 17 mm |
| K- 07 40 02 14 | R 3/8 | 12 mm | 28,5 | 48,4 | 17 mm |
| K- 07 40 02 15 | R 3/8 | 16 mm | 33,5 | 61,2 | 20 mm |
| K- 07 40 02 01 | R 1/2 | 6 mm | 20,0 | 39,5 | 21 mm |
| K- 07 40 02 02 | R 1/2 | 8 mm | 22,5 | 41,8 | 21 mm |
| K- 07 40 01 98 | R 1/2 | 10 mm | 26,9 | 49,9 | 21 mm |
| K- 07 40 01 99 | R 1/2 | 12 mm | 28,5 | 51,4 | 21 mm |
| K- 07 40 02 00 | R 1/2 | 16 mm | 33,5 | 63,2 | 21 mm |