

# K-STECKVERBINDU RED 10BAR

Reducers (pressure max. 10 bar)

**HANSA FLEX**

## Omadused

Töörõhk	Max. 10 bar
Rakendusvaldkond	Air, vacuum
soovitatud voolikud	PU or PA (nylon)
Vahendid	Compressed air and all gases or liquids that are compatible with the materials
Temperatuuri ulatus	-20 °C to +80 °C
Materjal	Plastic, Nickel plated brass
Surverõngas	Plastic



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Artikkel

Märgistus	vooliku välimise-Ø jaoks (mm)	L1 (mm)
K- 07 40 03 45	6 mm / 4 mm	31,0
K- 07 40 41 34	8 mm / 4 mm	36,5
K- 07 40 03 46	8 mm / 6 mm	34,5
K- 07 40 41 35	10 mm / 6 mm	40,2
K- 07 40 03 47	10 mm / 8 mm	39,4
K- 07 40 41 36	12 mm / 8 mm	45,0
K- 07 40 03 48	12 mm / 10 mm	44,2
K- 07 40 03 49	16 mm / 12 mm	49,6