


# K-ABSPV STECK GEW SCH OR

Shut-off valves, male thread, plug connection, flow direction to tube, parallel thread with O-ring

**HANSA FLEX**

## Omadused

Töörõhk	Max. 15 bar, coarse vacuum
Rakendusvaldkond	Air, vacuum
soovitatud voolikud	PU or PA (nylon)
Vahendid	Compressed air and all gases or liquids that are compatible with the materials
Temperatuuri ulatus	-20 °C to +80 °C
Tihenduspid	Parallel version: O-ring in housing, Conical version: thread coating
Materjal	Plastic, Nickel plated brass
Surverõngas	Plastic



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Artikkel

Märgistus	Keere	vooliku välimise-Ø jaoks (mm)	L1 (mm)	L2 (mm)	SW
K- 07 40 08 01	G 1/8	6 mm	58,0	42,6	14 mm
K- 07 40 08 02	G 1/8	8 mm	58,4	42,6	14 mm
K- 07 40 07 99	G 1/4	6 mm	59,8	42,6	12 mm
K- 07 40 08 00	G 1/4	8 mm	59,9	42,6	17 mm
K- 07 40 07 97	G 1/4	10 mm	70,9	47,0	17 mm
K- 07 40 07 98	G 1/4	12 mm	70,9	47,0	21 mm
K- 07 40 08 05	G 3/8	8 mm	61,4	42,6	17 mm
K- 07 40 08 03	G 3/8	10 mm	72,4	47,0	20 mm
K- 07 40 08 04	G 3/8	12 mm	71,9	47,0	21 mm
K- 07 40 07 95	G 1/2	10 mm	75,9	47,0	24 mm
K- 07 40 07 96	G 1/2	12 mm	75,4	47,0	24 mm