

# K-STECKVERBINDU 2

Straight push-in connector

**HANSA FLEX**

## Omadused

|                |                     |
|----------------|---------------------|
| Töörõhk        | Max. 16 bar         |
| Töötemperatuur | -20 °C to +150 °C   |
| Materjal       | Nikeldatud messing  |
| Surverõngas    | Nickel-plated brass |
| Pingutusrõngas | Stainless steel     |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Artikkel

| Märgistus      | vooliku välimise-Ø jaoks (mm) | L1<br>(mm) |
|----------------|-------------------------------|------------|
| K- 07 40 27 49 | 4 mm                          | 31,0       |
| K- 07 40 27 50 | 6 mm                          | 33,0       |
| K- 07 40 27 51 | 8 mm                          | 37,0       |
| K- 07 40 27 52 | 10 mm                         | 39,0       |
| K- 07 40 47 74 | 12 mm                         | 43,0       |
| K- 07 40 40 91 | 14 mm                         | 47,5       |