

# K-WERKST-SCHLAUCH SOFT

Workshop hose soft

**HANSA FLEX**

## Omadused

|              |                      |
|--------------|----------------------|
| Sisekiht     | Soft-PVC, black      |
| Sisestus     | Polüestrist vahekiht |
| Väliskiht    | Soft-PVC, blue       |
| Temperatuur  | -20 °C to +60 °C     |
| Rulli pikkus | 50 m                 |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

## Artikkel

| Märgistus      | Vooliku sise-Ø<br>(mm) | Vooliku välis-Ø<br>(mm) | Max. working pressure resistance at 23°C<br>(bar) | min. painderaadius<br>(mm) |
|----------------|------------------------|-------------------------|---|----------------------------|
| K- 07 10 10 33 | 6,3                    | 11,0                    | 15  | 23                         |
| K- 07 10 10 34 | 8,0                    | 13,0                    | 15  | 28                         |
| K- 07 10 10 35 | 9,0                    | 14,5                    | 15  | 32                         |
| K- 07 10 10 36 | 10,0                   | 15,5                    | 15  | 35                         |
| K- 07 10 10 37 | 12,7                   | 19,0                    | 15  | 45                         |
| K- 07 10 10 38 | 16,0                   | 23,0                    | 15  | 56                         |
| K- 07 10 10 39 | 19,0                   | 26,5                    | 15  | 67                         |
| K- 07 10 10 40 | 25,0                   | 33,5                    | 15  | 88                         |