

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Omadused

Sisekiht	Soft-PVC, black
Sisestus	Polüestrist vahekiht
Väliskiht	Soft-PVC, blue
Temperatuur	-20 °C to +60 °C
Rulli pikkus	50 m



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Artikkel

Märgistus	Vooliku sise-Ø (mm)	Vooliku välis-Ø (mm)	Max. working pressure resistance at 23°C (bar)	min. painderaadius (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88