


# K-DLV MULTI-LINK OHNE KUPPLU

Compressed air distributor, type »Multi-Link« without couplings, female thread

**HANSA FLEX**

## Omadused

|                            |   |
|----------------------------|---|
| <b>Töörõhk</b>             | Max. 16 bar   |
| <b>Temperatuuri ulatus</b> | -20 °C kuni +100 °C<br>(-20 °C to +80 °C quickconnect-safety couplings) |
| <b>Materjal</b>            | Galvanised steel / brass  |
| <b>Ühendus</b>             | G 1/2 female  |
| <b>Vahendid</b>            | Compressed air, non-corrosive gases                                     |
| <b>Tihendusmaterjal</b>    | NBR   |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Modular distributor system for flexible workplace design, can be rotated 180°. Equipped for 1 to 5 bleed units, optionally with:

- G 1/2 female threaded connection for individually adaption output segments,
- DN 7.6 standard quick disconnect couplings,
- DN 7.6 quick disconnectsafety couplings.

## Artikkel

| Märgistus      | Ühendus      | Veevõtuühik |
|----------------|--------------|-------------|
| K- 07 35 13 68 | G 1/2 female | 1           |
| K- 07 35 13 71 | G 1/2 female | 2           |
| K- 07 35 13 74 | G 1/2 female | 3           |
| K- 07 35 13 77 | G 1/2 female | 4           |
| K- 07 35 13 80 | G 1/2 female | 5           |