

# K-Y-WINKELVERSCH DRE AG-K

Male branch Y-elbows with outer hex, swivel type, conical male thread, coated

**HANSA FLEX**

## Omadused

<b>Töörõhk</b>	Max. 15 bar, coarse vacuum
<b>Rakendusvaldkond</b>	Air, vacuum
<b>soovitatud voolikud</b>	PU or PA (nylon)
<b>Vahendid</b>	Compressed air and all gases or liquids that are compatible with the materials
<b>Temperatuuri ulatus</b>	-20 °C to +80 °C
<b>Tihenduspid</b>	Conical version: thread coating
<b>Materjal</b>	Plastic, Nickel plated brass
<b>Surverõngas</b>	Plastic



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Artikkel

Märgistus	Keere	vooliku välimise-Ø jaoks (mm)	L1 (mm)	L2 (mm)	SW
K- 07 40 43 14	R 1/8	6 mm	24,0	25,0	12 mm
K- 07 40 43 13	R 1/4	8 mm	28,5	28,8	14 mm
K- 07 40 43 15	R 3/8	10 mm	33,7	34,8	19 mm
K- 07 40 43 12	R 1/2	12 mm	37,5	42,1	24 mm