

# K-T-STECK VERS DRE AG-K VA

Male branch tees, swivel type, conical male thread

**HANSA FLEX**

## Omadused

<b>Töö rõhk, pulseeriv</b>	Max. 10 bar
<b>Surve</b>	Max. 15 bar (depending on pipe quality)
<b>sobiv materjal</b>	PVDF, PTFE, stainless steel, PA, PU
<b>Tavaline</b>	R thread acc. to ISO 7-1
<b>Keskonnatemperatuur</b>	-20 °C to max. +150 °C (depending on pipe quality and diameter)
<b>Materjal</b>	Roostevaba teras 1.4404
<b>Tihendusmaterjal</b>	FKM



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Artikkel

Märgistus	Keere	vooliku välimise-Ø jaoks (mm)	L1 (mm)	L2 (mm)	SW
K- 07 40 24 59	R 1/8	4 mm	34,0	21,5	10 mm
K- 07 40 24 60	R 1/8	6 mm	42,0	24,5	13 mm
K- 07 40 24 61	R 1/8	8 mm	43,0	24,5	13 mm
K- 07 40 24 57	R 1/4	6 mm	42,0	28,5	14 mm
K- 07 40 24 58	R 1/4	8 mm	43,0	28,5	14 mm
K- 07 40 24 56	R 1/4	10 mm	50,0	32,0	16 mm
K- 07 40 24 62	R 3/8	10 mm	50,0	32,5	17 mm