

# K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

**HANSA FLEX**

## Omadused

|                       |  |
|-----------------------|--|
| <b>Rakendus</b>       | Air, gases, oils, greases, fuels, organic and inorganic substances |
| <b>Töötemperatuur</b> | -40 °C to +100 °C  |
| <b>Ühenduse liik</b>  | connection nipples and coupling NW 7,2                             |



## Vihje

Lisaandmed saate soovi korral.

## Kirjeldus

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Artikkel

| Märgistus      | Vooliku sise-Ø (mm) | Vooliku välis-Ø (mm) | Spiraali välis-Ø (mm) | Keermed | Max. working pressure resistance at 23°C (bar) | max tööpikkus (m) |
|----------------|---------------------|----------------------|-----------------------|---------|--|-------------------|
| K- 07 10 12 95 | 6,3                 | 7,9                  | 75                    | 15      | 13   | 2,5               |
| K- 07 10 12 96 | 6,3                 | 7,9                  | 75                    | 30      | 13   | 5,0               |
| K- 07 10 12 97 | 6,3                 | 7,9                  | 75                    | 45      | 13   | 7,5               |
| K- 07 10 12 65 | 7,9                 | 9,5                  | 115                   | 10      | 12   | 2,5               |
| K- 07 10 12 66 | 7,9                 | 9,5                  | 115                   | 20      | 12   | 5,0               |
| K- 07 10 12 67 | 7,9                 | 9,5                  | 115                   | 30      | 12   | 7,5               |
| K- 07 10 12 68 | 9,5                 | 11,8                 | 140                   | 8       | 11   | 2,5               |
| K- 07 10 12 69 | 9,5                 | 11,8                 | 140                   | 15      | 11   | 5,0               |
| K- 07 10 12 70 | 9,5                 | 11,8                 | 140                   | 23      | 11   | 7,5               |

## Lisatarvikud

|                                 |                                     |
|---------------------------------|-------------------------------------|
| <b>K-DREHBARE VERSCHR KNICK</b> | Swivel adapters with kink protector |
| <b>K-STARRE VERSCHRAUBUNG</b>   | Rigid adapters with kink protector  |