K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

Omadused

Rakendus	Air, gases, oils, greases, fuels, organic and inorganic substances
Töötemperatuur	-40 °C to +100 °C
Ühenduse liik	connection nipples and coupling NW 7,2



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Artikkel

Märgistus	Vooliku sise-Ø (mm)	Vooliku välis-Ø (mm)	Spiraali välis-Ø (mm)	Keermed	Max. working pressure resistance at 23°C (bar)	max tööpikkus (m)
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

Lisatarvikud

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector

Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.