

K-SPIR SCHL KUPPL SET STAND MS

Spiral hose and coupling kit with standard coupling and push-in plug, bare brass

HANSA FLEX

Omadused

Ühenduse liik connection nipples and coupling NW 7,2

Töötemperatuur -40 °C to +74 °C



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Artikkel

Märgistus	Vooliku sise-Ø (mm)	Vooliku välis-Ø (mm)	Välise keermes Ø (mm)	Max. working pressure resistance at 23°C (bar)	max tööpikkus (m)
K- 07 10 12 72	5,0	8,0	40	10	3,0
K- 07 10 12 74	5,0	8,0	40	10	6,0
K- 07 10 12 76	5,0	8,0	40	10	7,5
K- 07 10 12 81	6,3	9,5	60	10	3,0
K- 07 10 12 83	6,3	9,5	60	10	6,0
K- 07 10 12 85	6,3	9,5	60	10	7,5
K- 07 10 12 79	6,3	9,5	60	10	10,0
K- 07 10 12 90	8,0	12,0	80	9	3,0
K- 07 10 12 92	8,0	12,0	80	9	6,0
K- 07 10 12 94	8,0	12,0	80	9	7,5
K- 07 10 12 88	8,0	12,0	80	9	10,0

Lisatarvikud

K-DREHBARE VERSCHRAUBUNG Swivel adapters