K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

Omadused

Ühenduse liik	with pushbutton safety coupling NW 7,4 steel nipple galvanised
Töötemperatuur	-40 °C to +74 °C



Vihje

Lisaandmed saate soovi korral.

Kirjeldus

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.
Ei sobi kasutamiseks löögifunktsiooniga või impulsipõhiste tööriistadega!

Artikkel

Märgistus	Vooliku sise-Ø (mm)	Vooliku välis-Ø (mm)	Välise keerme Ø (mm)	Max. working pressure resistance at 23°C (bar)	max tööpikkus (m)
K- 07 10 12 71	5,0	8,0	40	10	3,0
K- 07 10 12 73	5,0	8,0	40	10	6,0
K- 07 10 12 75	5,0	8,0	40	10	7,5
K- 07 10 12 80	6,3	9,5	60	10	3,0
K- 07 10 12 82	6,3	9,5	60	10	6,0
K- 07 10 12 84	6,3	9,5	60	10	7,5
K- 07 10 12 78	6,3	9,5	60	10	10,0
K- 07 10 12 89	8,0	12,0	80	9	3,0
K- 07 10 12 91	8,0	12,0	80	9	6,0
K- 07 10 12 93	8,0	12,0	80	9	7,5
K- 07 10 12 87	8,0	12,0	80	9	10,0

Lisatarvikud

K-DREHBARE VERSCHRAUBUNG	Swivel adapters

Vaatamata põhjalikule kontrollile ei saa me vigade esinemist välistada ning ei vastuta olemasolevate andmete eest.