

K-T-STECK VB 20-63 SCHANH IG INFI

T-push-in connector Ø 20 mm – Ø 63 mm with integrated gooseneck and internal thread

HANSA FLEX

Omadused

| | |
|---------------------|-------------------------------------|
| Vahendid | Compressed air, vacuum, inert gases |
| Töö rõhk | -0,99 bar - 15 bar |
| Temperatuuri ulatus | -20 °C to +80 °C |
| Tihend | NBR |
| Korpus | Aluminium |
| Klemmrõngas | Stainless steel 1.4301 |
| Mutter | Aluminium |
| O-rõngas | NBR |
| Kinnitusrõngas | Technopolymer |



Artikkel

| Märgistus | Toru välis-Ø | Ühendus | A (mm) | B (mm) | C (mm) | E (mm) | L1 (mm) | L2 (mm) | SW (mm) | SW1 (mm) |
|----------------|--------------|---------|-----------|-----------|-----------|-----------|------------|------------|------------|-------------|
| K- 07 40 55 02 | 63 mm | G 1/2" | 13,5 | 57,5 | 88,0 | 94,0 | 203,0 | 53,0 | 80 | 75 |
| K- 07 40 55 01 | 63 mm | G 3/4 | 14,5 | 57,5 | 88,0 | 94,0 | 203,0 | 54,0 | 80 | 75 |
| K- 07 40 55 03 | 63 mm | G 1 | 17,5 | 57,5 | 88,0 | 94,0 | 203,0 | 56,5 | 80 | 75 |