


## Omadused

Rakendamine	with pressure gauge and silencer
min tööröhk	0.20 MPa
Pneumaatilise manomeetri ühendus	Rc 1/8
Pneumaatiliste manomeetrite ühenduste arv	2
max sisendröhk	0,1 to 1,0 MPa
Aine temperatuur	+2 °C to +50 °C
Keskonnatemperatuur	+2 °C bis +50 °C
Vahendid	Suruõhk



## Kirjeldus

Booster regulator, series VBA, increases pressure only where the force is inadequate because of a low network pressure (energy saving measure), no electricity supply necessary, longer service life: doubled compared to conventional model, lower operating noise level: 13 dB (A), improved operational reliability from inbuilt mesh filter on (IN connection) compressed air inlet, reduced condensation levels: air exhaust channels integrated directly into the cylinder tube, suitable for: compressed air, size 1/4, with pressure gauge and silencer, elbow, pneumatic connection: G 1/4, pneumatic connection pressure gauge: G 1/8, pneumatic connections pressure gauge: 2, flow rate 230 l/min, pressure boost 1:2, manually actuated pressure adjustment mechanism, test pressure: 3 MPa, max. operating pressure: 2 MPa, min. operating pressure: 0.2 MPa, media temperature: +2 to +50 °C, ambient temperature: +2 to +50 °C

## Artikkel

Märgistus	Pneumaatiline ühendus	Ehitussuurus	Röhu seadistusmehhanism	Röhu võimendamise vahekord	Läbivool (L/min)	max tööröhk (MPa)	Kontrollsurve (MPa)
K- 07 60 00 07	G 1/4	1/4	manually operated	1:2 to 1:4	70	2,00	3,00
K- 07 60 00 05	G 1/4	1/4	manually operated	1:2	230	2,00	3,00
K- 07 60 00 10	G 3/8	3/8	manually operated	1:2	1000	1,00	1,50