

K-W90 DRV AS-FS

Speed controllers, 90°, connection plug, with built-in indicator

HANSA FLEX

Omadused	
max töö rõhk	1 MPa
min töö rõhk	0.10 MPa
Väljundid	1
Juurdevoolude arv	1
Näiduakna joondamine	0°
Pöördnupu värv	Blue
Kontrollsurve	1,50 MPa
Juhtimine	Flow governing
Aine temperatuur	-5 °C to +60 °C (ohne Gefrieren)
Keskonnatemperatuur	-5 °C bis +60 °C (no freezing)
Vahendid	Suruõhk
Voolikumaterjal	polyamid, soft polyamid, polyurethane, FEP, PFA
Seeria	AS-FS
Muud andmed	large rotary knob with push-lock latch larger free space under the hose Lockable rotary knob, numeric display



Artikkel						
Märgistus	Ehitussuurus	Väljundi ühendus	Juurdevooluühendus	Rakendamine	Nöelapöörded	Kaal meetri kohta (kg)
K- 07 30 30 54	1	for hose outer-Ø2 mm	outer thread M 5	with sealing ring	8	0,007
K- 07 30 30 57	1	for hose outer-Ø3.2 mm	outer thread M 5	with sealing ring	8	0,007
K- 07 30 30 55	1	for hose outer-Ø4 mm	outer thread M 5	with sealing ring	8	0,007
K- 07 30 30 56	1	for hose outer-Ø6 mm	outer thread M 5	with sealing ring	8	0,008
K- 07 30 30 62	2	for hose outer-Ø3.2 mm	outer thread R 1/8	Teflon coated	10	0,007
K- 07 30 30 67	2	for hose outer-Ø3.2 mm	outer thread R 1/4	Teflon coated	10	0,023
K- 07 30 30 58	2	for hose outer-Ø4 mm	outer thread R 1/8	Teflon coated	10	0,013
K- 07 30 30 63	2	for hose outer-Ø4 mm	outer thread R 1/4	Teflon coated	10	0,023
K- 07 30 30 59	2	for hose outer-Ø6 mm	outer thread R 1/8	Teflon coated	10	0,014
K- 07 30 30 68	2	for hose outer-Ø6 mm	outer thread G 1/8	surface with sealing ring	10	0,014
K- 07 30 30 64	2	for hose outer-Ø6 mm	outer thread R 1/4	Teflon coated	10	0,023
K- 07 30 30 69	2	for hose outer-Ø6 mm	outer thread G 1/4	surface with sealing ring	10	0,023
K- 07 30 30 60	2	for hose outer-Ø8 mm	outer thread R 1/8	Teflon coated	10	0,015
K- 07 30 30 65	2	for hose outer-Ø8 mm	outer thread R 1/4	Teflon coated	10	0,024
K- 07 30 30 70	2	for hose outer-Ø8 mm	outer thread G 1/4	surface with sealing ring	10	0,024
K- 07 30 30 61	2	for hose outer-Ø10 mm	outer thread R 1/8	Teflon coated	10	0,016
K- 07 30 30 66	2	for hose outer-Ø10 mm	outer thread R 1/4	Teflon coated	10	0,025
K- 07 30 30 71	2	for hose outer-Ø10 mm	outer thread G 1/4	surface with sealing ring	10	0,025
K- 07 30 30 72	3	for hose outer-Ø6 mm	outer thread R 3/8	Teflon coated	10	0,038
K- 07 30 30 76	3	for hose outer-Ø6 mm	outer thread G 3/8	surface with sealing ring	10	0,038
K- 07 30 30 73	3	for hose outer-Ø8 mm	outer thread R 3/8	Teflon coated	10	0,038
K- 07 30 30 77	3	for hose outer-Ø8 mm	outer thread G 3/8	surface with sealing ring	10	0,038
K- 07 30 30 74	3	for hose outer-Ø10 mm	outer thread R 3/8	Teflon coated	10	0,029
K- 07 30 30 78	3	for hose outer-Ø10 mm	outer thread G 3/8	surface with sealing ring	10	0,029
K- 07 30 30 75	3	for hose outer-Ø12 mm	outer thread R 3/8	Teflon coated	10	0,041
K- 07 30 30 79	4	for hose outer-Ø10 mm	outer thread R 1/2	Teflon coated	10	0,062
K- 07 30 30 82	4	for hose outer-Ø10 mm	outer thread G 1/2	surface with sealing ring	10	0,062
K- 07 30 30 80	4	for hose outer-Ø12 mm	outer thread R 1/2	Teflon coated	10	0,064
K- 07 30 30 83	4	for hose outer-Ø12 mm	outer thread G 1/2	surface with sealing ring	10	0,064
K- 07 30 30 81	4	for hose outer-Ø16 mm	outer thread R 1/2	Teflon coated	10	0,068
K- 07 30 30 84	4	for hose outer-Ø16 mm	outer thread G 1/2	surface with sealing ring	10	0,068