

LKM HR ST DK

Pistikühenduse muhv (õhk) kaitsega

HANSA FLEX

Omadused

Tüüp	Kiirühendusmuhv
Ühendus 1	BSP-väliskeere, silindriline
Ühendus 2	
Tööõhk	maks 12 baari
Õhu läbivool	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Aine temperatuur	-20 °C to +70 °C
Korpus	Aluminium, anodised
Keere	Nickel-plated brass
Sisedetail	Stainless steel
Nupp, ventiil	Hardened, galvanised steel
Tihendusmaterjal	NBR



Vihje

Not suitable for hitting / pulsating tools.
Lisaandmed saate soovi korral.

Kirjeldus

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Artikkel

Märgistus	Ühendusniit	Ühendus	Pikkus (mm)	SW (mm)
LKM 06 HR ST DK	G 1/4 tolli - 19	G 1/4 male	70,5	21
LKM 10 HR ST DK	G 3/8" -19	G 3/8 male	70,0	21
LKM 13 HR ST DK	G 1/2" -14	G 1/2 male	72,5	25