

# LKM IR ST DK

Pistikühenduse muhv (õhk), kaitsega

**HANSA FLEX**

## Omadused

<b>Tüüp</b>	Kiirühendusmuhv
<b>Ühendus 1</b>	BSP-sisekeere, silindriline
<b>Ühendus 2</b>	
<b>Tööõhk</b>	maks 12 baari
<b>Õhu läbivool</b>	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
<b>Aine temperatuur</b>	-20 °C to +70 °C
<b>Korpus</b>	Aluminium, anodised
<b>Keere</b>	Nickel-plated brass
<b>Sisedetail</b>	Stainless steel
<b>Nupp, ventiil</b>	Hardened, galvanised steel
<b>Tihendusmaterjal</b>	NBR



## Vihje

Not suitable for hitting / pulsating tools.  
Lisaandmed saate soovi korral.

## Kirjeldus

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

## Artikkel

Märgistus	Ühendusniit	Ühendus	Pikkus (mm)	SW (mm)
LKM 06 IR ST DK	G 1/4 tolli - 19	G 1/4 female	71,5	21
LKM 10 IR ST DK	G 3/8" -19	G 3/8 female	75,5	21
LKM 13 IR ST DK	G 1/2" -14	G 1/2 female	77,5	24