

Omadused

Tüüp	Kiirühendusmuhv
Ühendus 1	Voolikühendus
Ühendus 2	
Töörõhk	maks 12 baari
Õhu läbivool	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Aine temperatuur	-20 °C to +70 °C
Korpus	Aluminium, anodised
Keere	Nickel-plated brass
Sisedetail	Stainless steel
Nupp, ventiil	Hardened, galvanised steel
Tihendusmaterjal	NBR



Vihje

Not suitable for hitting / pulsating tools.

Lisaandmed saate soovi korral.

Kirjeldus

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Artikel

Märgistus	Vooliku-ID jaoks (mm)	Ühendus	Pikkus (mm)	SW (mm)
LKM 06 MM ST DK	6	Stem, I.D. 6	88,5	21
LKM 09 MM ST DK	9	Stem, I.D. 9	88,5	21
LKM 13 MM ST DK	13	Stem, I.D. 13	88,5	21