


Caractéristiques				
Construction	Bagues coupantes avec joints toriques			
Norme	DIN 3861			
Matériau	Acier			
Traitement de surface	revêtement galvanisé			





Article					
Désignation	Série	Ø d2 (mm)	L1 (mm)	Joint torique	
SRDO 06 V	L/S	6	8,8	6 x 1	
SRDO 08 V	L/S	8	8,8	8 x 1	
SRDO 10 V	L/S	10	9,8	10 x 1	
SRDO 12 V	L/S	12	9,8	12 x 1	
SRDO 14 V	S	14	10,2	14 x 1	
SRDO 15 V	L	15	10,2	15 x 1	
SRDO 16 V	S	16	10,2	16 x 1	
SRDO 18 V	L	18	10,2	18 x 1	
SRDO 20 V	S	20	12,5	20 x 1	
SRDO 22 V	L	22	11,5	22 x 1	
SRDO 25 V	S	25	12,5	25 x 1	
SRDO 28 V	L	28	11,5	28 x 1	
SRDO 30 V	S	30	13,5	30 x 1	
SRDO 35 V	L	35	13,5	35 x 1	
SRDO 38 V	S	38	13,5	38 x 1	
SRDO 42 V	L	42	13,5	42 x 1	

Série : LL = très léger L = léger S = lourd $- \emptyset$ d2 = diamètre extérieur du tube