


Caractéristiques								
Plage de pression	3000 psi							
Norme	SAE J 518 C ISO 6162							
Conception	droit							
Construction	Plaque d'obturation SAE							
Fourniture	plaque d'obturation uniquement							
Matériau	S355J2G3 (C22)							
Traitement de surface	revêtement galvanisé							





Article													
Désignation	PB 10.9	Gabarit	A1	A2	G	С	D	E	F	Н	L	M (métrique)	M (unc)
	(bar)		(mm)										
BL 3001	350	1/2"	30,2	24,0	16	38,1	54	17,5	46	6,8	8,7	M 8 x 25	5/16" x 1.1/4"
BL 3002	350	3/4"	38,1	31,8	17	47,6	65	22,3	52	6,8	10,7	M 10 x 30	3/8" x 1.1/4"
BL 3003	315	1"	44,5	38,0	17	52,4	70	26,2	59	8,0	10,7	M 10 x 30	3/8" x 1.1/4"
BL 3004	250	1.1/4"	50,8	43,0	17	58,7	79	30,2	73	8,0	*1	*2	7/16" x 1.1/2"
BL 3005	200	1.1/2"	60,3	50,0	19	69,9	94	35,7	83	8,0	13,5	M 12 x 35	1/2" x 1.1/2"
BL 3006	200	2"	71,4	62,0	19	77,8	102	42,9	97	9,6	13,5	M 12 x 35	1/2" x 1.1/2"

PN = Pression nominale PB = Pression de service max.

^{*1) =} au choix 10,75 ou 12,0 ou 12,75 - *2) = au choix M 10 x 30 ou M 12 x 35