


Caractéristiques		
Raccord 1	filet ext. BSPT conique	
Étanchéité 1	à étanchéité par filetage	
Raccord 2	filet ext. BSPT conique	
Étanchéité 2	étanchéité par filetage	
Construction	Manchon fileté	
Conception	droit	
Matériau	Acier inoxydable	





1

G1	G2	SW <sub>(mm)</sub>
R 1/8" K	R 1/8" K	11
R 1/4" K	R 1/8" K	14
R 1/4" K	R 1/4" K	14
R 3/8" K	R 1/4" K	17
R 3/8" K	R 3/8" K	17
R 1/2" K	R 3/8" K	22
R 1/2" K	R 1/2" K	22
R 3/4" K	R 1/2" K	27
R 3/4" K	R 3/4" K	27
R 1" K	R 3/4" K	36
R 1" K	R 1" K	36
R 1 1/4" K	R 1" K	46
R 1 1/4" K	R 1,1/4" K	25
R 1 1/2" K	R 1,1/4" K	50
R 1 1/2" K	R 1 1/2" K	55
R 2" K	R 2" K	70
	R 1/8" K R 1/4" K R 1/4" K R 3/8" K R 3/8" K R 1/2" K R 1/2" K R 1/2" K R 3/4" K R 3/4" K R 1" K R 1" K R 1 1/4" K R 1 1/4" K R 1 1/4" K R 1 1/2" K	R 1/8" K R 1/8" K R 1/4" K R 1/8" K R 1/4" K R 1/4" K R 3/8" K R 1/4" K R 3/8" K R 3/8" K R 1/2" K R 1/2" K R 3/4" K R 1/2" K R 3/4" K R 1/2" K R 3/4" K R 3/4" K R 1" K R 3/4" K R 1" K R 1" K R 1 1/4" K R 1" K R 1 1/4" K R 1,1/4" K R 1 1/4" K R 1,1/4" K R 1 1/2" K R 1,1/4" K R 1 1/2" K R 1,1/4" K

SW = largeur de clé

0	ــ اــ	produits
(-amme	ne.	nrodilite
Jannin	u	DIOGUILO

G HRK Manchon fileté, Acier