


Caractéristiques	
Type de bague	Douille creuse
conçu pour	2SN (HD 200, HD 200T, HF 200, HW 200, HDB 200) 1SC (KP 400) 4SP (HD 400)
Matériau	Acier
Traitement de surface	revêtement galvanisé





Remarque

L'affectation de la bague dépend du type de tuyau.

Article							
DN*	Dimension	Pouce	D1 (mm)	D3 (mm)	LF (mm)		
5	3	3/16"	21	8,5	26,0		
6	4	1/4"	22	11,4	30,0		
8	5	5/16"	23	12,5	30,0		
10	6	3/8"	26	14,5	31,0		
12	8	1/2"	30	18,3	32,0		
16	10	5/8"	33	21,7	38,0		
19	12	3/4"	38	24,4	42,5		
25	16	1"	46	30,5	51,0		
31	20	1.1/4"	57	38,0	58,0		
38	24	1.1/2"	65	44,3	62,0		
51	32	2"	79	57,0	73,5		
60	40	2.3/8"	84	67,1	79,0		
76	48	3"	105	81,8	80,0		
	5 6 8 10 12 16 19 25 31 38 51 60	5 3 6 4 8 5 10 6 12 8 16 10 19 12 25 16 31 20 38 24 51 32 60 40	5 3 3/16" 6 4 1/4" 8 5 5/16" 10 6 3/8" 12 8 1/2" 16 10 5/8" 19 12 3/4" 25 16 1" 31 20 1.1/4" 38 24 1.1/2" 51 32 2" 60 40 2.3/8"	5 3 3/16" 21 6 4 1/4" 22 8 5 5/16" 23 10 6 3/8" 26 12 8 1/2" 30 16 10 5/8" 33 19 12 3/4" 38 25 16 1" 46 31 20 1.1/4" 57 38 24 1.1/2" 65 51 32 2" 79 60 40 2.3/8" 84	5 3 3/16" 21 8,5 6 4 1/4" 22 11,4 8 5 5/16" 23 12,5 10 6 3/8" 26 14,5 12 8 1/2" 30 18,3 16 10 5/8" 33 21,7 19 12 3/4" 38 24,4 25 16 1" 46 30,5 31 20 1.1/4" 57 38,0 38 24 1.1/2" 65 44,3 51 32 2" 79 57,0 60 40 2.3/8" 84 67,1		

DN = diamètre nominal, dimension nominale