

# PHF 100

Bague de serrage, TF 100

**HANSA FLEX**

## Caractéristiques

|                       |                      |
|-----------------------|----------------------|
| Type de bague         | Douille non creuse   |
| Matériau              | Acier                |
| Traitement de surface | revêtement galvanisé |



## Article

| Désignation | DN* | Dimension | Pouce | D1<br>(mm) | D3<br>(mm) | LF<br>(mm) |
|-------------|-----|-----------|-------|------------|------------|------------|
| PHF 104     | 5   | 3         | 3/16" | 13         | 8,3        | 30         |
| PHF 106     | 6   | 4         | 1/4"  | 15         | 10,6       | 32         |
| PHF 108     | 8   | 5         | 5/16" | 17         | 12,2       | 33         |
| PHF 110     | 10  | 6         | 3/8"  | 19         | 13,7       | 33         |
| PHF 113     | 12  | 8         | 1/2"  | 24         | 18,0       | 37         |
| PHF 116     | 16  | 10        | 5/8"  | 27         | 21,5       | 37         |
| PHF 120     | 19  | 12        | 3/4"  | 32         | 25,0       | 41         |
| PHF 125     | 25  | 16        | 1"    | 38         | 31,0       | 41         |

DN = diamètre nominal, dimension nominale

## Gamme de produits

PHF 100 VA Bague de serrage, TF 100, Acier inoxydable