


Caractéristiques				
Raccord 1	Filetage femelle UN/UNF			
Étanchéité 1	Cône intérieur 74°			
Abréviation	DKJ			
Norme	ISO 8434-2			
Matériau	Acier			
Traitement de surface	revêtement galvanisé			





Remarque

Les mamelons non endommagés peuvent être réutilisés.

DN	Dimension				
	Diffichsion	Pouce	G1	L1 (mm)	S1
6	4	1/4"	7/16" -20 UNF	40,0	14
6	4	1/4"	1/2" -20 UNF	40,0	17
10	6	3/8"	9/16" -18 UNF	45,0	19
12	8	1/2"	3/4" -16 UNF	51,0	22
12	8	1/2"	7/8" -14 UNF	65,0	27
16	10	5/8"	7/8" -14 UNF	65,0	27
19	12	3/4"	1 1/16" -12 UN	67,0	32
25	16	1"	1 5/16" -12 UN	70,0	41
	6 6 10 12 12 12 16	6 4 6 4 10 6 12 8 12 8 16 10 19 12	6 4 1/4" 6 4 1/4" 10 6 3/8" 12 8 1/2" 12 8 1/2" 16 10 5/8" 19 12 3/4"	6 4 1/4" 7/16" -20 UNF 6 4 1/4" 1/2" -20 UNF 10 6 3/8" 9/16" -18 UNF 12 8 1/2" 3/4" -16 UNF 12 8 1/2" 7/8" -14 UNF 16 10 5/8" 7/8" -14 UNF 19 12 3/4" 1 1/16" -12 UN	6 4 1/4" 7/16" -20 UNF 40,0 6 4 1/4" 1/2" -20 UNF 40,0 10 6 3/8" 9/16" -18 UNF 45,0 12 8 1/2" 3/4" -16 UNF 51,0 12 8 1/2" 7/8" -14 UNF 65,0 16 10 5/8" 7/8" -14 UNF 65,0 19 12 3/4" 1 1/16" -12 UN 67,0

Accessoires

ND ASR GE, RO, BL Bague de retenue pour mamelon embrochable