

Caractéristiques	3
Construction	Douilles de renforcement
Conception	droit
Matériau	Acier
Traitement de surface	revêtement galvanisé



Article					
Désignation	Ø d	Ø d1 (mm)	Diamètre ext. du tube x Épaisseur de paroi (mm)	Ø D (mm)	L (mm)
K 70-005-06-1	3,5	3	6 x 1	6	14,0
K 70-005-06-1.5	2,5	2	6 x 2	6	14,0
K 70-005-08-1	5,5	5	8 x 1	8	14,0
K 70-005-08-1.5	4,5	4	8 x 2	8	14,0
K 70-005-08-2	3,5	3	8 x 2	8	14,0
K 70-005-10-1	7,5	7	10 x 1	10	14,0
K 70-005-10-1.5	6,4	6	10 x 2	10	14,0
K 70-005-10-2	5,5	5	10 x 2	10	14,0
K 70-005-12-1.5	8,8	8	12 x 2	12	14,0
K 70-005-12-2	7,5	7	12 x 2	12	14,0
K 70-005-15-1	12,5	12	15 x 1	15	14,5
K 70-005-15-1.5	11,5	11	15 x 2	15	14,5
K 70-005-18-1.5	14,5	14	18 x 2	18	14,5
K 70-005-18-2	13,5	13	18 x 2	18	14,5