

K-FLAMM SCHLAUCH

Flame tube

HANSA FLEX

Caractéristiques

Domaine d'utilisation welding equipment
welding robots
welding machines
Welding Related areas

Couleur noir

Température min. -40 °C

Température max. 90 °C



Informations supplémentaires

- Flame retardant according to UL94 V2/V0
- Welding-spark resistant
- Halogen-free according to EN 50267-2-1 (complies with IEC 60754-1)
- LABS free (free from paint-adhesion inhibiting substances)
- UV-resistant
- can be used with drag chains
- flexible
- resistant to bending
- very good wear resistance
- plasticiser free

Article

Désignation	Ø intérieur (mm)	Ø extérieur (mm)	Épaisseur de paroi (mm)	Rayon de courbure min. (mm)	Max. working pressure resistance at 23°C (bar)	Longueur des rou- leaux (m)
K- 07 10 13 27	2,0	4,0	1,0	7	27	50
K- 07 10 13 28	4,0	6,0	1,0	8	20	50
K- 07 10 13 29	4,0	8,0	2,0	9	23	50
K- 07 10 13 30	6,0	10,0	2,0	15	21	50
K- 07 10 13 31	8,0	12,0	2,0	26	18	50
K- 07 10 13 32	10,0	14,0	2,0	38	13	50
K- 07 10 13 33	11,0	16,0	2,5	65	15	50