

# K-FLAMM SCHLAUCH

Flame tube

**HANSA FLEX**

## Caractéristiques

**Domaine d'utilisation** welding equipment  
welding robots  
welding machines  
Welding Related areas

**Couleur** noir

**Température min.** -40 °C

**Température max.** 90 °C



## Informations supplémentaires

- Flame retardant according to UL94 V2/V0
- Welding-spark resistant
- Halogen-free according to EN 50267-2-1 (complies with IEC 60754-1)
- LABS free (free from paint-adhesion inhibiting substances)
- UV-resistant
- can be used with drag chains
- flexible
- resistant to bending
- very good wear resistance
- plasticiser free

## Article

Désignation	Ø intérieur (mm)	Ø extérieur (mm)	Épaisseur de paroi (mm)	Rayon de courbure min. (mm)	Max. working pressure resistance at 23°C (bar)	Longueur des rou- leaux (m)
<b>K- 07 10 13 27</b>	2,0	4,0	1,0	7	27	50
<b>K- 07 10 13 28</b>	4,0	6,0	1,0	8	20	50
<b>K- 07 10 13 29</b>	4,0	8,0	2,0	9	23	50
<b>K- 07 10 13 30</b>	6,0	10,0	2,0	15	21	50
<b>K- 07 10 13 31</b>	8,0	12,0	2,0	26	18	50
<b>K- 07 10 13 32</b>	10,0	14,0	2,0	38	13	50
<b>K- 07 10 13 33</b>	11,0	16,0	2,5	65	15	50