K-MANO 1

Pressure gauges (CrNi steel type / safety housing)

HANSA FLEX

Caractéristiques

Type	232.30
Fabrication	Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)
Application	For gaseous or liquid, corrosive and crystallising mediawhich do not have high viscosity, also in corrosive atmosphere
Classe de qualité	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
Température de fluide	max. +200 °C
Température ambiante	-40 °C to +60 °C
Boîtier	CrNi steel
Lumière	Laminated safety glass Ø 63 = Polycarbonate



Remarque

Autres informations sur demande.

Description

Safety version with more fracture-resistant separating wall

Article

Désignation	Plage de mesure	Ø (mm)	Raccord
K- 07 20 07 15	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 07 16	0 - 1.6 bar	63,0	G 1/4"
K- 07 20 07 17	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 07 18	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 07 19	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 07 20	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 07 21	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 07 22	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 07 23	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 07 24	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 07 25	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 01 97	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 01 98	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 01 99	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 02 00	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 02 01	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 02 02	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 02 03	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 02 04	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 02 05	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 02 06	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 02 07	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 02 08	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 02 09	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 02 10	0 - 400.0 bar	100,0	G 1/2"

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.