

# K-MANO ABSPV ZAPF SPAN MUF PRUEFFL

Pressure gauge valves, male - female/female, with test flange 60 x 25 x 10

**HANSA FLEX**

## Caractéristiques

|  |  |
|--|--|
| <b>Pression de service</b>               | max. 250 bar brass, max. 400 bar steel/<br>stainless steel         |
| <b>Température</b>                       | Max. +120 °C with brass/steel;<br>Max. +200 °C for stainless steel |
| <b>Matériau tous composants</b>          | Stainless steel  |
| <b>Matériau étanche</b>                  | PTFE   |
| <b>Boîtier</b>                           | Brass, black-finished steel or stainless<br>steel 1.4571           |
| <b>Volant</b>                            | Plastic  |
| <b>Écrou-raccord, manchon de serrage</b> | Steel  |
| <b>Broche de vanne, cône de vanne</b>    | Stainless steel  |



## Remarque

Autres informations sur demande.

## Description

They are used as shut-off or reducing elements for pressure gauges when measuring liquids, gases or steam.

## Article

| Désignation    | Filets | PN (bar) | SW<br>(mm) | Matériau        |
|----------------|--------|----------|------------|-----------------|
| K- 07 20 11 34 | G 1/2  | 250      | 27         | Laiton          |
| K- 07 20 11 33 | G 1/2  | 400      | 27         | Stainless steel |