

K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

HANSA FLEX

Caractéristiques

| | |
|------------------------|---|
| Température de service | -60 °C to +100 °C (PA 12) |
| Caractéristiques | Resistant to corrosion, vibration, impact, ageing, high pressures and heat |
| Longueur de tube | 3 m |
| Conditionnement | 10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units! |
| Matériau | Polyamid PA 12, hard (according to DIN 73378) |



Remarque

Operating pressure with 2.5 x overpressure safety!

Autres informations sur demande.

Description

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Article

| Désignation | Ø ext. du tube (mm) | Ø int. de tube (mm) | Pression de service maxi à 20 °C (bar) | Couleur |
|----------------|---------------------|---------------------|--|---------|
| K- 07 10 04 57 | 12 | 9 | 38 | bleu |
| K- 07 10 04 59 | 12 | 9 | 38 | noir |
| K- 07 10 04 61 | 15 | 12 | 25 | bleu |
| K- 07 10 04 63 | 15 | 12 | 25 | noir |
| K- 07 10 04 65 | 18 | 14 | 28 | bleu |
| K- 07 10 04 67 | 18 | 14 | 28 | noir |
| K- 07 10 04 69 | 22 | 18 | 22 | bleu |
| K- 07 10 04 71 | 22 | 18 | 22 | noir |
| K- 07 10 04 73 | 28 | 23 | 20 | bleu |
| K- 07 10 04 75 | 28 | 23 | 20 | noir |