K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

Caractéristiques

Température de service	-60 °C to +100 °C (PA 12)
Caractéristiques	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Longueur de tube	3 m
Conditionnement	10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!
Matériau	Polyamid PA 12, hard (according to DIN 73378)



Remarque

Operating pressure with 2.5 x overpressure safety!
Autres informations sur demande.

Description

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Article

Désignation	Ø ext. du tube (mm)	Ø int. de tube (mm)	Pression de service maxi à 20 °C (bar)	Couleur
K- 07 10 04 57	12	9	38	bleu
K- 07 10 04 59	12	9	38	noir
K- 07 10 04 61	15	12	25	bleu
K- 07 10 04 63	15	12	25	noir
K- 07 10 04 65	18	14	28	bleu
K- 07 10 04 67	18	14	28	noir
K- 07 10 04 69	22	18	22	bleu
K- 07 10 04 71	22	18	22	noir
K- 07 10 04 73	28	23	20	bleu
K- 07 10 04 75	28	23	20	noir

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.