

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Caractéristiques

Température de service	-60 °C to +100 °C (PA 12)
Caractéristiques	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Longueur de tube	3 m
Conditionnement	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Matériau	Polyamid PA 12, hard (according to DIN 73378)



Remarque

Operating pressure with 2.5 x overpressure safety!

Autres informations sur demande.

Description

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Article

Désignation	Ø ext. du tube (mm)	Ø int. de tube (mm)	Pression de service maxi à 20 °C (bar)	Couleur
K- 07 10 04 56	12	9	38	bleu
K- 07 10 04 58	12	9	38	noir
K- 07 10 04 60	15	12	25	bleu
K- 07 10 04 62	15	12	25	noir
K- 07 10 04 64	18	14	28	bleu
K- 07 10 04 66	18	14	28	noir
K- 07 10 04 68	22	18	22	bleu
K- 07 10 04 70	22	18	22	noir
K- 07 10 04 72	28	23	20	bleu
K- 07 10 04 74	28	23	20	noir