

# K-SPIR SCHL B DREH VERSCHRAU

Spiral hose, with swivel adapter fitted at both ends and kink protector

**HANSA FLEX**

## Caractéristiques

|                        |  |
|------------------------|--|
| Application            | Air, gases, oils, greases, fuels, organic and inorganic substances |
| Température de service | -40 °C to +100 °C  |
| Type de raccordement   | connection nipples and coupling NW 7,2                             |



## Remarque

Autres informations sur demande.

## Description

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Article

| Désignation    | Ø tuyau intérieur (mm) | Ø tuyau extérieur (mm) | Filets | Ø spirale extérieure (mm) | Spires | Max. working pressure resistance at 23°C (bar) | Longueur de travail maxi (m) |
|----------------|------------------------|------------------------|--------|---------------------------|--------|--|------------------------------|
| K- 07 10 07 34 | 3,1                    | 4,7                    | R 1/8  | 38                        | 36     | 22   | 2,5                          |
| K- 07 10 07 35 | 3,1                    | 4,7                    | R 1/8  | 38                        | 72     | 22   | 5,0                          |
| K- 07 10 07 36 | 3,1                    | 4,7                    | R 1/8  | 38                        | 108    | 22   | 7,5                          |
| K- 07 10 07 37 | 4,8                    | 6,3                    | R 1/4  | 75                        | 15     | 16   | 2,5                          |
| K- 07 10 07 38 | 4,8                    | 6,3                    | R 1/4  | 75                        | 30     | 16   | 5,0                          |
| K- 07 10 07 39 | 4,8                    | 6,3                    | R 1/4  | 75                        | 45     | 16   | 7,5                          |
| K- 07 10 07 40 | 6,3                    | 7,9                    | R 1/4  | 75                        | 15     | 13   | 2,5                          |
| K- 07 10 07 41 | 6,3                    | 7,9                    | R 1/4  | 75                        | 30     | 13   | 5,0                          |
| K- 07 10 07 42 | 6,3                    | 7,9                    | R 1/4  | 75                        | 45     | 13   | 7,5                          |
| K- 07 10 07 28 | 7,9                    | 9,5                    | R 1/4  | 115                       | 10     | 12   | 2,5                          |
| K- 07 10 07 29 | 7,9                    | 9,5                    | R 1/4  | 115                       | 20     | 12   | 5,0                          |
| K- 07 10 07 30 | 7,9                    | 9,5                    | R 1/4  | 115                       | 30     | 12   | 7,5                          |
| K- 07 10 07 31 | 9,5                    | 11,8                   | R 3/8  | 140                       | 8      | 11   | 2,5                          |
| K- 07 10 07 32 | 9,5                    | 11,8                   | R 3/8  | 140                       | 15     | 11   | 5,0                          |
| K- 07 10 07 33 | 9,5                    | 11,8                   | R 3/8  | 140                       | 23     | 11   | 7,5                          |

## Accessoires

|                          |                                     |
|--------------------------|-------------------------------------|
| K-DREHBARE VERSCHR KNICK | Swivel adapters with kink protector |
| K-STARRE VERSCHRAUBUNG   | Rigid adapters with kink protector  |