

# K-SPIR SCHL DREH VERSCHRAU

Spiral hose, with swivel adapter and kink protector

**HANSA FLEX**

## Caractéristiques

Température de service -40 °C to +74 °C



## Remarque

Autres informations sur demande.

## Description

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Article

| Désignation    | Filets | Ø tuyau intérieur<br>(mm) | Ø tuyau extérieur<br>(mm) | Ø spire extérieure<br>(mm) | Max. working pressure resistance at 23°<br>C<br>(bar) | Longueur de travail maxi<br>(m) |
|----------------|--------|---------------------------|---------------------------|----------------------------|---|---------------------------------|
| K- 07 10 07 19 | G 1/4  | 5,0                       | 8,0                       | 40                         | 10  | 3,0                             |
| K- 07 10 07 20 | G 1/4  | 5,0                       | 8,0                       | 40                         | 10  | 6,0                             |
| K- 07 10 07 21 | G 1/4  | 5,0                       | 8,0                       | 40                         | 10  | 7,5                             |
| K- 07 10 07 22 | G 1/4  | 6,3                       | 9,5                       | 60                         | 10  | 3,0                             |
| K- 07 10 07 23 | G 1/4  | 6,3                       | 9,5                       | 60                         | 10  | 6,0                             |
| K- 07 10 07 24 | G 1/4  | 6,3                       | 9,5                       | 60                         | 10  | 7,5                             |
| K- 07 10 12 77 | G 1/4  | 6,3                       | 9,5                       | 60                         | 10  | 10,0                            |
| K- 07 10 07 25 | G 3/8  | 8,0                       | 12,0                      | 80                         | 9   | 3,0                             |
| K- 07 10 07 26 | G 3/8  | 8,0                       | 12,0                      | 80                         | 9   | 6,0                             |
| K- 07 10 07 27 | G 3/8  | 8,0                       | 12,0                      | 80                         | 9   | 7,5                             |
| K- 07 10 12 86 | G 3/8  | 8,0                       | 12,0                      | 80                         | 9   | 10,0                            |

## Accessoires

K-DREHBARE VERSCHRAUBUNG Swivel adapters