# K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

## Caractéristiques

| | |
|---|---|
| **Type de raccordement** | with kink protector, swivel type |
| **Température de service** | -40 °C to +74 °C |



## Remarque

Autres informations sur demande.

## Description

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Article

| Désignation | Filets | Ø tuyau intérieur (mm) | Ø tuyau extérieur (mm) | Ø spire extérieure (mm) | Max. working pressure resistance at 23° C (bar) | Longueur de travail maxi (m) |
|---|---|---|---|---|---|---|
| **K- 07 10 07 43** | G 1/4 | 6,3 | 9,5 | 42 | 14 | 3,0 |
| **K- 07 10 07 44** | G 1/4 | 6,3 | 9,5 | 42 | 14 | 6,0 |
| **K- 07 10 07 45** | G 1/4 | 6,3 | 9,5 | 42 | 14 | 7,5 |
| **K- 07 10 07 46** | G 3/8 | 8,0 | 12,0 | 55 | 14 | 3,0 |
| **K- 07 10 07 47** | G 3/8 | 8,0 | 12,0 | 55 | 14 | 6,0 |
| **K- 07 10 07 48** | G 3/8 | 8,0 | 12,0 | 55 | 14 | 7,5 |

## Accessoires

| | |
|---|---|
| **K-DREHBARE VERSCHRAUBUNG** | Swivel adapters |

*En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.*