


K-SPIR SCHL KUPPL SET

Spiral hose and coupling kits

HANSA FLEX

Caractéristiques

| | |
|----------------------------|---|
| Pression de service | max. 10 bar (to the temperature +20 °C); max. 7 bar (at temperature +40 °C); max. 5 bar (at temperature +60 °C) |
| Accouplement | High quality hand quick release coupling of steel for high flow rates For demanding applications with high mechanical wear |
| Tuyau en spirale | Polyurethane |



Remarque

Autres informations sur demande.

Description

For pneumatic applications in challenging industrial environments. High-quality, one-hand quick disconnect coupling made of steel with safety lock to prevent unintentional disconnection. For complex applications susceptible to severe mechanical wear. The outer layer of the hose, which is designed to withstand flying sparks and scorching, has special spark protection. It is therefore ideal for all pneumatic tools used in welding processes.

Article

| Désignation | Dimension de tuyau | Ø spirale (mm) | Longueur de travail (m) |
|-----------------------|--------------------|-------------------|----------------------------|
| K- 07 10 07 56 | 10 mm x 6,5 mm | 52 | 4,0 |
| K- 07 10 07 57 | 10 mm x 6,5 mm | 52 | 6,0 |
| K- 07 10 07 58 | 12 mm x 8 mm | 65 | 8,0 |