

K-VSEH 3-KRAFT

Receptacle combinations »3-Kraft«

HANSA FLEX

Caractéristiques

| | |
|--------------------------------|--|
| Boîtier | Amaplast with hinged cover |
| Intégré dans le boîtier | Hanging eyelets, wall mounting fixing and standing feet |
| Fabrication | Pre-wired |
| Entrées de conduite | Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection or grabrails (all introductions to break) |
| Indice de protection | IP 44 |



Remarque

Autres informations sur demande.

Description

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Article

| Désignation | Garnissage | Couleur |
|----------------|---|---------|
| K- 07 10 03 50 | 3 Schuko socket 16 A 2p + E 230 V | jaune |
| K- 07 10 03 49 | 2 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V | argent |

Accessoires

| | |
|--------------------------------------|--|
| K-VT 2 KUPPL 7,2 STECKNIP MS | Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8 |
| K-ZUBEH VSEH 3 KRAFT AIRKRAFT | Accessories for receptacle combinations »3-Kraft« and »airkraft« |