

Caractéristiques

Boîtier	Amaplast with hinged cover
Intégré dans le boîtier	Hanging eyelets, wall mounting fixing and standing feet
Sauvegarde	Beneath transparent lid (4 MW)
Fabrication	Pre-wired
Entrées de conduite	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection(all openings can be cut out)
Indice de protection	IP 44



Remarque

Autres informations sur demande.

Description

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Article

Désignation	Garnissage	Couleur
K- 07 10 03 52	4 Schuko socket 16 A 2p + E 230 V	jaune
K- 07 10 03 51	3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	argent

Accessoires

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«