


# K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

**HANSA FLEX**

## Caractéristiques

|                                  |  |
|----------------------------------|--|
| <b>Pression de service</b>       | See table. All values referred to a medium temperature of 50 °C (static working pressure)  |
| <b>Débit d'air</b>               | 440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8),<br>1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar) |
| <b>Température de fluide</b>     | -20 °C to +90 °C   |
| <b>Boîtier, douille</b>          | POM (Delrin), white  |
| <b>Vanne</b>                     | Stainless steel 1.4305   |
| <b>Ressort, circlip, sphères</b> | stain less steel   |
| <b>Matériau étanche</b>          | NBR  |



## Remarque

Autres informations sur demande.

## Description

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Article

| Désignation    | Raccord      | Pression de service (bar) | Longueur (mm) | VN   | SW (mm) |
|----------------|--------------|---------------------------|---------------|------|---------|
| K- 07 40 39 58 | G 1/8 female | 15,0                      | 29,5          | 4,3  | 14      |
| K- 07 40 39 59 | G 1/4 female | 15,0                      | 35,3          | 6,0  | 19      |
| K- 07 40 39 60 | G 3/8 female | 15,0                      | 39,0          | 7,5  | 22      |
| K- 07 40 39 61 | G 1/2 female | 10,0                      | 48,0          | 11,0 | 27      |
| K- 07 40 39 62 | G 3/4 female | 10,0                      | 60,0          | 13,0 | 36      |