

K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Caractéristiques

Pression de service	0 - 35 bar, maximum static working pressure (non-pulsating)
Débit d'air	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Température de fluide	-20 °C to +100 °C
Manchon de déverrouillage	Anodised aluminium
Ressort, circlip, sphères	stain less steel
Matériau étanche	NBR



Remarque

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Autres informations sur demande.

Description

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Article

Désignation	Raccord	Couleur	Longueur (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	vert	45,0	14
K- 07 35 06 81	G 1/4 male	vert	47,0	17
K- 07 35 06 82	G 1/8 female	vert	45,0	14
K- 07 35 06 83	G 1/4 female	vert	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	bleu	45,0	14
K- 07 35 06 89	G 1/4 male	bleu	47,0	17
K- 07 35 06 90	G 1/8 female	bleu	45,0	14
K- 07 35 06 91	G 1/4 female	bleu	47,0	17
K- 07 35 06 92	G 1/8 male	rouge	45,0	14
K- 07 35 06 93	G 1/4 male	rouge	47,0	17
K- 07 35 06 94	G 1/8 female	rouge	45,0	14
K- 07 35 06 95	G 1/4 female	rouge	47,0	17