
K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

Caractéristiques

Pression de service	0 - 35 bar, maximum static working pressure (non-pulsating)
Débit d'air	1.800 l/min (at 6 bar and Δp = 0.5 bar)
Température de fluide	-20 °C to +100 °C
Boîtier	Brass
Vanne	Die-cast zinc, nickel-plated
Manchon de déverrouillage	Anodised aluminium
Ressort, circlip, sphères	stain less steel
Matériau étanche	NBR



Remarque

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Autres informations sur demande.

Description

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Article

Désignation	Raccord	Couleur	Longueur (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	vert	57,5	19
K- 07 35 08 02	G 3/8 male	vert	57,5	19
K- 07 35 08 03	G 1/4 female	vert	55,5	19
K- 07 35 08 04	G 3/8 female	vert	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	bleu	57,5	19
K- 07 35 08 10	G 3/8 male	bleu	57,5	19
K- 07 35 08 11	G 1/4 female	bleu	55,5	19
K- 07 35 08 12	G 3/8 female	bleu	54,5	19
K- 07 35 08 13	G 1/4 male	rouge	57,5	19
K- 07 35 08 14	G 3/8 male	rouge	57,5	19
K- 07 35 08 15	G 1/4 female	rouge	55,5	19
K- 07 35 08 16	G 3/8 female	rouge	54,5	19

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.