K-FEDERSTOESSEL
Spring plungers

Caractéristiques

Application	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Température min.	0 °C
Température max.	80 °C
Raccord d'aspiration	M 3 female
Fabrication	Spring plunger with high-strength steel rodl, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
Course du ressort	5,0 mm



Remarque
Autres informations sur demande.

Description
Suitable for all round or oval suction pads in our standard range.

Article

Désignation	Raccord aspiration	Longueur (mm)	Charge verticale (N/m2)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400

En dépit du soin apporté aux vérifications, nous ne pouvons garantir une absence totale d'erreur et ne saurions être tenus responsables des indications contenues.