

K-DRS MDR 5 O ENTLASTU VENT

»MDR 5« pressure switches, without unloading valve / on/off switch / motor protection circuit, with flange 1/4

HANSA FLEX

Caractéristiques

| | |
|-------------------------------|------------------------------------|
| Température de fluide | -5 °C to +80 °C |
| Pression de coupure maxi | 16 bar |
| Capacité de commutation | 5,5 kW |
| Type de contact | NC (3-pole) |
| Fréquence de commutation maxi | 120 (electrical), 600 (mechanical) |
| Indice de protection | IP 54 |



Remarque

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Autres informations sur demande.

Description

Three-phase version

Informations relatives à la commande

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Informations supplémentaires

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Article

| Désignation | Raccord air comprimé | Plage de réglage |
|----------------|----------------------|------------------|
| K- 07 30 24 24 | G 1/2 | 2,0 - 11,0 bar |
| K- 07 30 24 26 | G 1/2 | 2,5 - 16,0 bar |