

# K-3 BKR L VA

3-way ball valves, L-bore

## Caractéristiques

|                              |                                     |
|------------------------------|-------------------------------------|
| Pression de service          | max. 63 bar                         |
| Température de service       | max. 160 °C                         |
| Perçage                      | forme L                             |
| Valeurs indicatives          | Up to 40 °C: 63 bar, 150 °C: 28 bar |
| Joint d'étanchéité           | RTFE                                |
| Manette                      | Stainless steel                     |
| Robinet à boisseau sphérique | Stainless steel 1.4408              |



## Remarque

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)  
Autres informations sur demande.

## Description

With L-bore, reduced bore. Version for sealing on all sides with integrated ISO flange plate (ISO 5211). The lever can be turned 360° to allow several switching variants.

## Informations relatives à la commande

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Informations supplémentaires

G thread acc. DIN EN ISO 228-1

## Article

| Désignation    | DN | Filets  | A<br>(mm) | B<br>(mm) | L<br>(mm) | Ø D<br>(mm) |
|----------------|----|---------|-----------|-----------|-----------|-------------|
| K- 07 30 15 02 | 8  | G 1/4   | 114,0     | 73,0      | 80,0      | 11,0        |
| K- 07 30 15 03 | 10 | G 3/8   | 114,0     | 73,0      | 80,0      | 11,0        |
| K- 07 30 15 04 | 15 | G 1/2   | 114,0     | 73,0      | 80,0      | 12,5        |
| K- 07 30 15 05 | 20 | G 3/4   | 133,0     | 78,0      | 87,0      | 16,0        |
| K- 07 30 15 06 | 25 | G 1     | 133,0     | 83,0      | 100,0     | 20,0        |
| K- 07 30 15 07 | 32 | G 1 1/4 | 187,0     | 92,0      | 123,0     | 25,0        |
| K- 07 30 15 08 | 40 | G 1 1/2 | 187,0     | 98,0      | 142,0     | 31,8        |
| K- 07 30 15 09 | 50 | G 2     | 187,0     | 126,0     | 170,0     | 38,1        |