

# K-S-BKR M ENTL

Safety ball valves

**HANSA FLEX**

## Caractéristiques

|  |                           |
|--|---------------------------|
| Température de service                 | 0 °C to +60 °C            |
| Description filetage                   | Rp thread acc. to ISO 7-1 |
| Matériau étanche                       | PTFE                      |
| Boîtier, sphère, broche, presse-étoupe | Nickel-plated brass       |
| Manette                                | Die-cast aluminium, black |
| Matériau                               | sealing: PTFE             |



## Remarque

Autres informations sur demande.

## Description

2/2-way brass safety ball valves. Specially designed for pneumatic applications. The ball valve shuts off the supply side and relieves the application into the atmosphere.

## Article

| Désignation    | DN | Filets   | A<br>(mm) | B<br>(mm) | L<br>(mm) | Pression de service maxi à 20 °C<br>(bar) |
|----------------|----|----------|-----------|-----------|-----------|---|
| K- 07 30 21 08 | 8  | Rp 1/4   | 100,0     | 61,0      | 52,0      | 12  |
| K- 07 30 21 09 | 10 | Rp 3/8   | 100,0     | 61,0      | 55,0      | 12  |
| K- 07 30 21 10 | 15 | Rp 1/2   | 100,0     | 64,0      | 69,0      | 12  |
| K- 07 30 21 11 | 20 | Rp 3/4   | 120,0     | 76,0      | 77,0      | 12  |
| K- 07 30 21 12 | 25 | Rp 1     | 120,0     | 80,0      | 89,0      | 12  |
| K- 07 30 21 13 | 32 | Rp 1 1/4 | 150,0     | 98,0      | 103,0     | 12  |
| K- 07 30 21 14 | 40 | Rp 1 1/2 | 150,0     | 104,0     | 114,0     | 12  |
| K- 07 30 21 15 | 50 | Rp 2     | 175,0     | 119,0     | 134,0     | 12  |