

K-3 BKR L EINFACHWIRKEND

Stainless steel ball valves, 3-way, with single-acting actuator, L-bore

HANSA FLEX

Caractéristiques

| | |
|--|--|
| Construction | Pneumatic actuators, in double- or single acting version, with integrated end-position feedback |
| Perçage | forme L |
| Pression de service | max. 63 bar (depending on temperature and nominal size) |
| Température de service | -20 °C to +70 °C |
| Angle de rotation | 90 ° |
| Boîtier | Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S |
| Pression de commande | 5.5 bar |
| Adaptateur vanne | Acc. to NAMUR |
| Entraînement | aluminium eloxed |
| Étanchéité de l'entraînement | NBR |
| Robinet à boisseau sphérique | Stainless steel 1.4401, with ISO-flange plate |
| Étanchéité robinet à boisseau sphérique | PTFE/FKM |



Remarque

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Autres informations sur demande.

Description

3-way cock, reduced bore

Informations supplémentaires

Other T-positions on request

Article

| Désignation | DN | Filets | Mise en place | A (mm) | B (mm) | D (mm) | L (mm) | SW (mm) |
|----------------|----|----------|---------------|-----------|-----------|-----------|-----------|------------|
| K- 07 30 03 11 | 15 | Rp 1/2 | L 1 | 133,0 | 139,0 | 20,0 | 73,0 | 27 |
| K- 07 30 03 12 | 20 | Rp 3/4 | L 1 | 137,0 | 159,0 | 23,0 | 80,0 | 32 |
| K- 07 30 03 13 | 25 | Rp 1 | L 1 | 161,0 | 174,5 | 28,5 | 90,0 | 41 |
| K- 07 30 03 14 | 32 | Rp 1 1/4 | L 1 | 161,0 | 179,5 | 36,5 | 90,0 | 50 |
| K- 07 30 03 15 | 40 | Rp 1 1/2 | L 1 | 180,0 | 185,0 | 37,0 | 105,0 | 55 |
| K- 07 30 03 16 | 50 | Rp 2 | L 1 | 209,0 | 213,5 | 47,5 | 115,0 | 71 |